

509.459.6656 • 1821 W. 5th Avenue • Suite 102 • Spokane, WA 99201 • Rian@MojoPrint.Solutions

# FILE SUBMISSION GUIDELINES

#### **Email Artwork to:**

Rian@MojoPrint.Solutions

#### Larger files can be uploaded to our FTP Site:

MojoPrint.Solutions

## **Acceptable Digital Art:**

- Print-Ready PDF (PREFERRED METHOD)\*
- EPS
- High-resolution JPG or TIFF\*\*
- Adobe Illustrator
- Adobe InDesign
- Adobe Photoshop
- notoshop you are submitting files from a different
- Microsoft Word
- version of CS, please save accordingly,
- Microsoft Publisher
- or submit a print-ready PDF.

We are currently running Adobe CS6. If

If you you would prefer to submit a file in a different format than the ones listed above, please contact us.

\* A "Print-Ready" file should include any bleeds & crop marks. All die lines (cut, fold, score) should be removed. If you need to send these as a reference, please create a separate file. \*\* JPEG and TIFF files are "raster" images (pixels, like a photo). For that reason, we do not recommend their use for any text, and particularly for small and/or narrow fonts.

#### Logos:

Logos should be vector, and may be in PDF, EPS or AI format. Logos that are being printed two-color on an ink press must be in either of these formats so that they can be correctly separated into spot colors. JPG & TIFF files are acceptable for digital production; we recommend at least 300 DPI resolution, at 100% of the size used in your document.

#### Fonts

If using the Adobe Pro Suite, we recommend fonts be converted to outlines (or curves) so as to avoid font issues. If using custom or non-standard fonts in MS Word or Publisher, please provide a PDF file or a copy of the font(s) used to avoid font issues.

## **PDF Files**

When creating PDF files from any program, we recommend that you review the PDF file carefully before submitting your file to ensure the format did not change.

## **CMYK & Spot Colors**

All files intended for digital OR full-color printing should be set up as CMYK (spot color OK for digital print).

All files intended for specific PMS ink color printing should be setup as spot colors.

If you do not know how to convert files to CMYK or Spot Colors, we will be happy to assist you.

#### **Linked Images**

If submitting the native file, regardless of program, we recommend that you include all linked images. If using Adobe Pro Suite, you may embed the linked images.

# **Bleeds & Margins**

If a file has bleeds (meaning any part of an image reaches the edge of the cut size) then the file must be submitted with at least a .125" bleed around each edge (bleed image should extended beyond cut size).

On all pieces, we recommend at least a .125" safe margin inside the cut size for all live matter (logos, text) to allow for cutting.

#### **Transparencies**

Documents created in Adobe Pro Suite can be very complex, resulting in many layers, clipping paths, transparencies and overlapping images/elements. To minimize the potential for issues, we highly recommend flattening all transparencies when creating your PDF file.